

RG 59/U (RGB) Miniature Multi-Channel Precision Cable

75 Ohm High-End Coaxial Cables for Video, Analog & Monitor Applications

Product Construction:**Conductors:**

- Solid bare copper per ASTM B3

Insulation/Core:

- Foam polyethylene (PE)

Shield:

- Tinned copper braid
- Flexfoil® shield

Jacket:

- Outer jacket: matte finish thermoplastic elastomer (TPE)
- Inner jacket: flame-retardant PVC

Packaging:

- Please contact Customer Service for packaging and color options

Applications:

- Suitable for RF signal transmission
- Broadcast
- HDTV
- Video-analog/digital
- Monitor applications

CATALOG NUMBER	AWG SIZE NOM. DCR	INSULATION MATERIAL		SHIELD COVERAGE NOM SHLD DCR	NOMINAL O.D.		NOMINAL CAPACITANCE		VELOCITY OF PROPAGATION, %	NOMINAL IMPEDANCE, Ω	NOMINAL ATTENUATION	
		in	mm		in	mm	pF/ft	pF/m			MHz	dB/100'
RG 59/U (RGB) RISER RATED												
395035-3 RG 59/U Type UL CMR c(UL) CMG 	26 Ga. 3/Cond. Stranded (7/34) Bare Copper 39.7 Ω/Mft.	Foam PE		Bi-Metal Foil +95% Tinned Copper Braid Shield 8.6 Ω/Mft.	Inner: Flame- Retardant PVC		17.30	56.74	78	75	1	0.56
		0.089	2.26		Outer: TPE Matte						10	1.48
											50	3.20
											100	5.18
						200	6.95					
						400	9.36					
						540	10.88					
						1000	15.79					
						2250	23.69					
						3000	27.35					
395035-4 RG 59/U Type UL CMR c(UL) CMG 	26 Ga. 4/Cond. Stranded (7/34) Bare Copper 39.7 Ω/Mft.	Foam PE		Bi-Metal Foil +95% Tinned Copper Braid Shield 8.6 Ω/Mft.	Inner: Flame- Retardant PVC		17.30	56.74	78	75	1	0.56
		0.089	2.26		Outer: TPE Matte						10	1.48
											50	3.20
											100	5.18
						200	6.95					
						400	9.36					
						540	10.88					
						1000	15.79					
						2250	23.69					
						3000	27.35					
395035-5 RG 59/U Type UL CMR c(UL) CMG 	26 Ga. 5/Cond. Stranded (7/34) Bare Copper 39.7 Ω/Mft.	Foam PE		Bi-Metal Foil +95% Tinned Copper Braid Shield 8.6 Ω/Mft.	Inner: Flame- Retardant PVC		17.30	56.74	78	75	1	0.56
		0.089	2.26		Outer: TPE Matte						10	1.48
											50	3.20
											100	5.18
						200	6.95					
						400	9.36					
						540	10.88					
						1000	15.79					
						2250	23.69					
						3000	27.35					

Data subject to change.